

Contents

Mechanical Sensors

- Tactile image detection using a 1k-element silicon pressure sensor array. 397
S. Sugiyama, K. Kawahata, M. Yoneda and I. Igarashi (Aichi-ken, Japan)
- New magnetoelastic force sensor using amorphous alloys 401
J. Seekircher and B. Hoffmann (Karlsruhe, F.R.G.)
- New piezoelectric transducers for internal strain measurement 406
C. Cavalloni and P. Engeler (Winterthur, Switzerland)
- Integrated stylus-force gauge 410
Y.-C. Tai and R. S. Muller (Berkeley, CA, U.S.A.)
- An angle-of-rotation sensor using flip-flop photodetecting techniques 414
P. J. French, H. Muro, Y. Hiramoto (Yokosuka, Japan) and W. Lian (Delft, The Netherlands)
- An electronic wind meter based on a silicon flow sensor 420
B. W. van Oudheusden and J. H. Huijsing (Delft, The Netherlands)
- High-sensitivity 2-D flow sensor with an etched thermal isolation structure. 425
B. W. van Oudheusden and A. W. van Herwaarden (Delft, The Netherlands)
- Liquid transport in micron and submicron channels 431
J. Pfahler, J. Harley, H. Bau and J. Zemel (Philadelphia, PA, U.S.A.)
- Fiber-optic position sensor 435
Y. Takamatsu, K. Tomita, J. Takagi and T. Yamashita (Kyoto, Japan)
- Fiber-optic dual-coil sensor for simultaneous measurements of mechanical displacement and temperature change 438
K. Oka, T. Takeda and Y. Ohtsuka (Hokkaido, Japan)
- Microdisplacement sensor using a polarization-maintaining optical fiber. 442
H. Kitajima, J. Takagi and T. Yamashita (Kyoto, Japan)
- High-resolution optical displacement pickup operable at 175 °C 445
K. Nishida and M. Kondo (Kanagawa-ken, Japan)

Radiant Sensors

- High-density Schottky-barrier infrared image sensor. 451
M. Kimata, M. Denda and N. Tsubouchi (Hyogo, Japan)
- A retinal CCD sensor for fast 2D shape recognition and tracking. 456
I. Debusschere, E. Bronckaers, C. Claeys (Leuven, Belgium), G. Kreider, J. Van der Spiegel (Philadelphia, PA, U.S.A.), G. Sandini (Genoa, Italy), P. Dario, F. Fantini (Pisa, Italy), P. Bellutti and G. Soncini (Trento, Italy)
- Monolithic heteroepitaxial infrared sensor arrays on Si for thermal imaging applications. . . . 461
J. Masek, C. Maissen, H. Zogg and S. Blunier (Zurich, Switzerland)
- Basic characteristics of an infrared CCD with a pyroelectric gate. 465
M. Okuyuma, Y. Togami, H. Taniguchi, Y. Hamakawa (Osaka, Japan), M. Kimita and M. Denda (Hyogo, Japan)
- A new type of photosensitive capacitor with MPNIM structure. 469
Zhu Changchun and Liu Junhua (Xi'an, China)
- A thin-film bolometer for radiation thermometry at ambient temperature 473
W. Lang, K. Kühl (Munich, F.R.G.) and E. Obermeier (Berlin, F.R.G.)

Low-temperature operating silicon bolometers for nuclear radiation detection	478
G.-A. Racine, R. A. Buser, N. F. de Rooij (Neuchâtel, Switzerland), G. Stucki, R. Stucki and K. Pretzl (Berne, Switzerland)	
High-purity silicon soft X-ray imaging sensor array.	482
S. A. Audet, E. M. Schooneveld, S. E. Wouters and M. H. Kim (Delft, The Netherlands)	
Silicon nuclear radiation detectors of a-Si:H/c-Si heterojunction structure with sensitive large area or array area	487
M. Yabe (Tokyo, Japan) and N. Sato (Kanagawa, Japan)	
A highly-sensitive silicon microphotosensor	494
He Mincai, Chen Bingruo and Huang Qijun (Hubei, China)	
Metallic thin-film diffraction grating as a new type of radiation detector	498
V. I. Konov, P. I. Nikitin, D. G. Satjukov and S. A. Uglov (Moscow, U.S.S.R.)	
Pyroelectric infrared sensor arrays based on the polymer PVDF	503
G. Mader and H. Meixner (Munich, F.R.G.)	
Pyroelectric infrared array sensors made of <i>c</i> -axis-oriented La-modified PbTiO ₃ thin films. . .	508
R. Takayama, Y. Tomita, J. Asayama, K. Nomura and H. Ogawa (Osaka, Japan)	
Compatible integration of radiation detectors and transistors.	513
S. E. Wouters, S. A. Audet and M. H. Kim (Delft, The Netherlands)	
Contactless lifetime measurement in processed and preprocessed high-purity silicon radiation sensors	517
T. Otaredian and S. A. Audet (Delft, The Netherlands)	
High-resolution reflective photointerrupter.	522
M. Takeuchi, N. Atarashi, Y. Ito and M. Shimura (Kyoto, Japan)	
In-process inspection of IC under packaging by single laser beam and photosensors	525
I. Kimura (Saga-shi, Japan)	
An array-type PSD (position-sensitive detector) for light pattern measurement	529
A. Kawasaki, M. Goto, H. Yashiro and H. Ozaki (Kawasaki, Japan)	
On the position response of a position-sensitive detector (PSD) irradiated with multiple light beams.	534
A. Kawasaki and M. Goto (Kawasaki, Japan)	
A linear high-performance PSD displacement transducer with microcontroller interfacing . . .	538
G. C. M. Meijer and R. Schrier (Delft, The Netherlands)	
An integrated position sensor using JFETs as a buffer for PSD output signal.	544
H. Muro and P. J. French (Yokosuka, Japan)	
A silicon ultraviolet detector	553
R. S. Popović, K. Solt, U. Falk and Z. Stoessel (Zug, Switzerland)	
Photodiodes in silicon with an electrically-programmable UV response	559
R. F. Wolffenbuttel (Delft, The Netherlands)	
Optimizing the performance of spectrally selective photodiodes by simulated annealing techniques	564
A. S. Glass (Zug, Switzerland) and R. Morf (Zurich, Switzerland)	
Planar epitaxial avalanche photodiodes with enhanced blue sensitivity for scintillation detectors	570
O. Boslau and W. von Münch (Stuttgart, F.R.G.)	
Performance of an integrated silicon colour sensor with a digital output in terms of response to colours in the colour triangle	574
R. F. Wolffenbuttel and G. de Graaf (Delft, The Netherlands)	
A new transducer for color distinction.	581
H. Kato, M. Kojima (Nagoya-shi, Japan), A. Kondo, N. Morishita and Y. Inagaki (Gifu-shi, Japan)	

Interfaces

- A scaled electronically-configurable multichannel recording array 589
J. Ji, K. Najafi and K. D. Wise (Ann Arbor, MI, U.S.A.)
- Sensor array with A/D conversion based on flip-flops 592
W. Lian, S. E. Wouters, D. A. Aupers and P. M. Sarro (Delft, The Netherlands)
- Variable spatial filtering detector with high rate of weighting function change 598
S. Inagaki (Kanagawa, Japan), T. Yamaura and A. Kobayashi (Tokyo, Japan)
- Analog circuit for interfacing silicon optical sensors and driving a dual-slope A/D converter
for logarithmic read-out 603
R. F. Wolffenbuttel (Delft, The Netherlands)
- Self-adapting multiple microphone system 610
K. Takahashi and H. Yamasaki (Tokyo, Japan)
- Dynamic calibration of sensors using EEPROMs 615
P. P. L. Regtien and P. J. Trimp (Delft, The Netherlands)

Thermal Sensors

- Integrated thermopile sensors 621
A. W. van Herwaarden, D. C. van Duyn, B. W. van Oudheusden and P. M. Sarro (Delft,
The Netherlands)
- Cu/Pd thin-film thermopile as a temperature and hydrogen sensor 631
M. Baciocchi, A. Bearzotti, M. Gentili, A. Lucchesini, C. Caliendo, E. Verona and
A. D'Amico (Rome, Italy)
- Smart temperature sensor in CMOS technology 636
P. Krummenacher and H. Oguey (Neuchâtel, Switzerland)
- Bipolar-process-compatible lateral-field silicon temperature sensor with charge injection 639
R. F. Wolffenbuttel (Delft, The Netherlands)
- Design of a CMOS temperature sensor with current output 645
A. Kölling, F. Bak, P. Bergveld and E. Seevinck (Enschede, The Netherlands)
- High-resolution thin-film temperature sensor arrays for medical applications 650
G. Urban, A. Jachimowicz, F. Kohl, H. Kuttner, F. Olcaytug, H. Kamper, F. Pittner,
E. Mann-Buxbaum, T. Schalkhammer, O. Prohaska and M. Schönauer (Vienna, Aus-
tria)
- A new class of integrated thermal oscillators with duty-cycle output for application in
thermal sensors 655
Y. Pan, F. R. Riedijk and J. H. Huijsing (Delft, The Netherlands)
- Temperature monitoring for prevention of pressure sores 660
T. Tamura, J. Zhou and T. Togawa (Tokyo, Japan)
- Ultrasonic distributed temperature sensor 663
W. K. Kulczyk, G. W. Smith and G. A. Jackson (Enfield, U.K.)
- A SAW delay-line oscillator as a high-resolution temperature sensor 670
J. Neumeister, R. Thum and E. Lüder (Stuttgart, F.R.G.)

Ultrasonic Sensors

- A novel junction surface acoustic wave detector in silicon 675
J. C. Haartsen and A. Venema (Delft, The Netherlands)
- Improvement of integrated ultrasonic transducer sensitivity 679
J.-H. Mo, A. L. Robinson, F. L. Terry, Jr., D. W. Fitting and P. L. Carson (Ann Arbor,
MI, U.S.A.)
- B-mode imaging using Si ultrasonic image sensor 683
K. Higuchi, K. Suzuki, H. Tanigawa, T. Horiguchi and N. Takanashi (Kanagawa, Japan)

Sandwich-layer transducer — a versatile design for ultrasonic transducers operating in air . . .	687
T. Möckl, V. Mągori and C. Eccardt (Munich, F.R.G.)	
Liquid—solid phase transition detection with acoustic plate mode sensors: application to icing of surfaces	693
R. C. Hughes, S. J. Martin, G. C. Frye and A. J. Ricco (Albuquerque, NM, U.S.A.)	
Flexural plate-wave gravimetric chemical sensor	700
S. W. Wenzel and R. M. White (Berkeley, CA, U.S.A.)	
Viscosity and density sensing with ultrasonic plate waves	704
B. A. Martin, S. W. Wenzel and R. M. White (Berkeley, CA, U.S.A.)	
A theoretical approach for a low diffraction ultrasonic transducer	709
C. Martin, J. Y. Chapelon and D. Cathignol (Lyon, France)	
Monitoring photo-polymerization of thin films using SH acoustic plate mode sensors	712
S. J. Martin and A. J. Ricco (Albuquerque, NM, U.S.A.)	
A P(VDF—TrFE)-based integrated ultrasonic transducer	719
A. S. Fiorillo, J. Van der Spiegel, P. E. Bloomfield and D. Esmail-Zandi (Philadelphia, PA, U.S.A.)	
Optical beam deflector using a piezoelectric bimorph actuator	726
T. Ono (Kawasaki, Japan)	
Piezo film: form and function	729
R. H. Brown (Dunfermline, U.K.)	
Magnetic Sensors	
Differential Hall IC for gear-tooth sensing	737
H. Jasberg (Munich, F.R.G.)	
A low-offset spinning-current Hall plate	743
P. J. A. Munter (Delft, The Netherlands)	
Monolithic silicon magnetic compass	747
K. Maenaka, M. Tsukahara and T. Nakamura (Toyohashi, Japan)	
A symmetrical vertical Hall-effect device	751
U. Falk (Zug, Switzerland)	
On-chip metal deformation measurements: a magnetic approach	754
A. Bossche and J. R. Mollinger (Delft, The Netherlands)	
Rotation of base region Hall field in magnetotransistors	758
A. Nathan and H. P. Baltes (Zurich, Switzerland)	
Integrated magnetic sensors	762
T. Nakamura and K. Maenaka (Toyohashi, Japan)	
3-D magnetic field sensor realized as a lateral magnetotransistor in CMOS technology	770
Lj. Ristić, M. T. Doan and M. Paranjape (Edmonton, Alta., Canada)	
Low-frequency noise in modulation-doped AlAs/GaAs superlattice dual-drain magnetic sensors	776
A. Nathan, H. P. Baltes, R. Castagnetti (Zurich, Switzerland), Y. Sugiyama (Tsukuba, Japan) and D. R. Briglio (Edmonton, Alta., Canada)	
Integrated silicon magnetotransistors: high sensitivity or high resolution?	780
A. Nathan and H. P. Baltes (Zurich, Switzerland)	
A novel integrated 3-D DMOS magnetic vector sensor based on BCD technology	786
Lai Zongsheng, Liu Yi, Wu Guangli and Jiang Hao (Shanghai, China)	
Comparison of noise properties of different magnetic-field semiconductor integrated sensors	790
A. Chovet (Grenoble, France), Ch. S. Roumenin (Sofia, Bulgaria), G. Dimopoulos and N. Mathieu (Grenoble, France)	

A thin-film magnetoresistive angle detector	795
K. J. M. Eijkel, J. W. Wieberdink, J. H. J. Fluitman, T. J. A. Popma, P. Groot and H. Leeuwis (Enschede, The Netherlands)	
Fluxgate sensor in planar microtechnology	799
T. Seitz (Zug, Switzerland)	
Revolution counter using magnetic bubble device for multi-turn absolute encoder	803
F. Kohsaka, T. Iino, Y. Kudou, Y. Sakamaki and T. Ueda (Tokyo, Japan)	
Universal magneto-operational amplifier (MOP).	807
K. Maenaka, H. Okada and T. Nakamura (Toyahashi, Japan)	
Hybrid magneto-temperature sensor using contacts on a $\text{YBa}_2\text{Cu}_3\text{O}_{7-\delta}$ superconductor . . .	812
T. Aoyama, S. Miyake, T. Kusaka, Y. Suzuki, T. Yotsuya and S. Ogawa (Osaka, Japan)	

